



Custom
Engineered
Solutions for
Tomorrow

Reed Technology



standexmeder.com

Reed Switches in Comparison with Mechanical Switches

Specifications	Reedschalter	Mechanical Microswitch
Sensing Distance - Touch	Up to 40mm effectively	Touch (zero distance)
Power Required all the Time	No	No
Input Requirements	External magnetic field >5 gauss min.	Mechanical Force
Hysteresis	Ability to adjust, to meet design request	Differential Travel (D.T.)
Life Expectancy: Low Level	10 ¹⁰ cycles	10 ⁶ cycles
Switching Voltage	Up to 200V (10,000V available)	250VAC
Switching Current/Carry Current	Up to 3A/Up to 5A	Up to 25A
Switching Load Minimum	No load required (μ V/pA)	50mW
Switching Load Maximum	Up to 100 Watts	Up to 5,000 Watts
Insulation Resistance	10 ¹⁴ Ohm	10 ⁹ Ohm
Contact Resistance	50 milliohm	100 milliohm
Noise	Almost no switching noise	Switching Noise
Overload	Very sensitive	Insensitive
Hermeticity	Yes	No
General	Galvanic isolation (air gap)	Galvanic Isolation (air gap)
Assembly	20,000 pcs	5,000 pcs